

<b>LUKAS</b>	<b>eDRAULIC Cutter</b>			<b>NFPA</b>
	<b>S 799 E2 90-20-43</b>			
	Technical Data			
<b>Non metric dimensions for reference only!</b>				
<b>Nomenclature</b>		<b>Value</b>	<b>Unit</b>	<b>Remark</b>
<b>Dimensions</b>	L x W x H	1010 x 276 x 281 39.8 x 10.9 x 11.1	mm in.	closed; w/o battery
<b>Cutting performance</b>		Ø45 Ø1.77	mm in.	
<b>Opening width at tips</b>		204 8.03	mm in.	at tips
<b>Ambient temperature</b>		-20 ... +55 -4 ... +131	°C °F	
<b>Weight</b>		25,3 55.8	kg lbs.	incl. hydraulic fluid, w/o battery <i>inkl. Hydraulikflüssigkeit, ohne Akku</i>
<b>Weight battery</b>		0,9 2	kg lbs.	
<b>Protection class</b>		IP 54		
<b>Opening / closing time</b>	>	2	s	w/o load
<b>Noise pressure level</b>	idle mode max. load	69 71	dB(A) dB(A)	
<b>Rechargeable battery 1 / 2</b>		25,2 2,6 / 5,0	V DC Ah	Li-Ion, optional accessory
<b>Current consumption</b>		12 40	A A	idle mode max. load
<b>NFPA 1936 Specification</b>		A9/B9/C9/D9/E9/F5		
<b>Operating pressure</b>		70 10,000	MPa psi	
<b>Note:</b>				
Since all values are subject to tolerances, minor differences may occur between the data of your equipment and this data.				
<b>LUKAS Hydraulik GmbH</b>	Weinstraße 39 • D-91013 Erlangen • Tel.+49 9131/698-0 • Fax +49 9131/698-394			

Änderungen vorbehalten / Subject to revision